



Flexible COB LED Strip - High Density

Model Number: COB-RBL-XX (IP20) & COB-STRIP-XX (IP65)



COLOR/CCT

	WARM WHITE 2700K: 2700 Kelvin Temp, 290/ft lumens
	WARM WHITE: 3000 Kelvin Temp, 305/ft lumens
	NEUTRAL WHITE: 4000 Kelvin Temp, 320/ft lumens
	COOL WHITE: 5000 Kelvin Temp, 425/ft lumens

TECHNICAL PARAMETERS

Voltage	24VDC	IP Rating	IP 20 / IP65
Wattage	60W/5M	Dimmable	Yes, if used with a dimmable driver
Cutttable	Every 2"	Product Length	5M (16.25 feet), 15M (49 feet)
LED Diode	SMD 2110	Colors Available	Warm White 2700K, Warm White, Neutral White, Cool White
CRI	CRI > 90	Kelvin Temp	2700K (WW-2700K), 3000K (WW), 4000K (NW), 5000K (CW)
Certificate	ETL Approved		

ITEM ID & DESCRIPTION

IP20 (5M)	IP20 (15M)	IP65 (15M)	
COB-RBL-WW-2700K	COB-RBL-WW-2700K-15	COB-STRIP-WW-2700K-15	24VDC, CCT 2700K, Warm White 2700K
COB-RBL-WW-3000K	COB-RBL-WW-3000K-15	COB-STRIP-WW-3000K-15	24VDC, CCT 3000K, Warm White
COB-RBL-WW-3500K			24VDC, CCT 3500K, Warm White
COB-RBL-NW	COB-RBL-NW-15	COB-STRIP-NW-15	24VDC, CCT 4000K, Neutral White
COB-RBL-CW	COB-RBL-CW-15	COB-STRIP-CW-15	24VDC, CCT 5000K, Cool White

CONNECTORS

	1. WC-COB-8	PCB to Wire Connector, 6" Wire, for 8mm PCB
	2. WC-COB-10	PCB to Wire Connector, 6" Wire, for 10mm PCB
	3. JC-COB-8	Splice Connector for 8mm PCB
	4. JC-COB-10	Splice Connector for 10mm PCB
	5. CC-COB-8	Corner Connector, 6" Wire, for 8mm PCB
	6. CC-COB-10	Corner Connector, 6" Wire, for 10mm PCB
	7. WC-COB-IP65-N	PCB to Wire Connector, No Wire, for IP65 10mm PCB
	8. JC-COB-IP65-N	Splice Connector, No Wire, for IP65 10mm PCB

DIMMABLE MAGNETIC LED DRIVERS

FL-60W-24V-LED-DIM1	FL-200W-24V-LED-DIM1
FL-100W-24V-LED-DIM1	FL-300W-24V-LED-DIM1
FL-150W-24V-LED-DIM1	FL-600W-24V-LED-DIM1

DIMMABLE ELECTRONIC LED DRIVERS

FL-60W-24V-LED-DIM3	FL-60W-24V-LED-DIM4
FL-100W-24V-LED-DIM3	FL-120W-24V-LED-DIM4
FL-150W-24V-LED-DIM3	FL-200W-24V-LED-DIM4
FL-200W-24V-LED-DIM3	FL-300W-24V-LED-DIM4
FL-300W-24V-LED-DIM3	