

FUTURA LIGHTING

Futura LED Under Cabinet Lights

Prod. Names: FL-1204 & FL-1207 Series



DIA: 2 3/4 in. | H: 1/2 in. | Cutout: 2 1/2 in.

Features:

- Long Lifetime:** > 50,000 hours
- Energy Conservation:** Save 80% more energy compared with traditional lighting fixtures
- Lumen maintenance:** 70% at 30,000 hrs.
- Surface mounted:** With small screws
- Wattage:** 3 watts CREE or Edison LED
- Wire length:** 3 feet
- Connector:** AMP
- Mounting:** Recessed or surface
- Dimmable:** Yes

Ref. Name & Colors:

- Ref. Name: FL-1204 (12VDC)**
- FL-1204 01ED WW** (Black Finish / Edison Warm White)
 - FL-1204 02ED WW** (White Finish / Edison Warm White)
 - FL-1204 05ED WW** (Brushed Chrome Finish / Edison Warm White)
 - FL-1204 05ED W** (Brush Chrome Finish / Edison Cool White)
 - FL-1204 03 WW** (Gold Finish / CREE Warm White)
 - FL-1204 04 WW** (Chrome Finish / CREE Warm White)
 - FL-1204 05 WW** (Brushed Chrome Finish / CREE Warm White)
 - FL-1204 05 W** (Brushed Chrome Finish / CREE Cool White)

Compatible LED Drivers:

LED-10W-12VDC	(10W, Input 120V 50/60Hz, Output 12VDC Non-Dimmable)
LED-25W-12VDC	(25W, Input 85-277V 50/60Hz, Output 12VDC Non-Dimmable)
LED-60W-12VDC	(60W, Input 100-277V 60 Hz, Output 12VDC Non-Dimmable)
LED-100W 12VDC	(100W, Input 120-277V 50/60Hz, Output 12VDC Waterproof Non-Dimmable)
FL-36W-LED-6B	(36W, Input 100-240V 50/60Hz, Output 12VDC Non-Dimmable w/ 6-Light Distribution Box)
FL-36W-12V-LED-DIM	(36W, Input 120V 50/60Hz, Output 12VDC Dimmable)
*FL-50W-12V-LED-DIM	(50W, Input 120V 50/60Hz, Output 12VDC Dimmable)
FL-60W-12V-LED-DIM	(60W, Input 120V 50/60Hz, Output 12VDC Dimmable)

*New small-sized unit: (LxWxH) 6" x 2" x 1 3/8"



DIA: 2 1/8 in. | H: 3/4 in.

Features:

- Tap Body to Turn On/Off, Non-Dimmable**
- Energy Conservation:** Save 80% more energy compared with traditional lighting fixtures
- Lumen maintenance:** 70% at 30,000 hrs.
- Surface mounted:** With 3M Foam Tape
- Wattage:** 2 watts output equal to 10W halogen
- Wire length:** 16 inches
- Warm White:** 3000°K | **Cool White:** 6000°K
- With built-in constant voltage LED circuit board, powered by 10-30VDC**
- Adopts 24-SMD NICHIA LED and a plastic front lens matte**

Ref. Name & Colors:

- Ref. Name: FL-1207 (10-30VDC)**
- FL-1207 02 WW** (White Body, White White LED)
 - FL-1207 02 W** (White Body, Cool White LED)
 - FL-1207 05 WW** (Silver Body Body, Warm White LED)
 - FL-1207 05 W** (Silver Body, Cool White)

Compatible LED Drivers:

LED-10W-12VDC	(10W, Input 120V 50/60Hz, Output 12VDC Non-Dimmable)
LED-25W-12VDC	(25W, Input 85-277V 50/60Hz, Output 12VDC Non-Dimmable)
LED-60W-12VDC	(60W, Input 100-277V 60 Hz, Output 12VDC Non-Dimmable)
LED-100W 12VDC	(100W, Input 120-277V 50/60Hz, Output 12VDC Waterproof Non-Dimmable)
FL-60W-LED-PLUGIN	(60W, Input 100-240V 50/60Hz, Output 12VDC Non-Dimmable)
FL-1206T	(60W, Input 120V-240V 50/60Hz, Output 12VDC Waterproof Non-Dimmable)
FL-1210W	(100W, Input 120V-240V 50/60Hz, Output 12VDC Waterproof Non-Dimmable)
FL-1220W	(200W, Input 120V-240V 50/60Hz, Output 12VDC Waterproof Non-Dimmable)