


FUTURA LIGHTING



INTRODUCING OUR NEW FL-1207 02 & FL-1207 05

FEATURES:

Tap Body to Turn On/Off

Energy Conservation: Save 80% more energy compared with traditional lighting fixtures

Eco-friendly: No UV or RF interface, no Mercury or Lead

Lumen maintenance: 70% at 30,000 hours

Surface mounted: with 3M Foam Tape

2 Watts: Output equal to 10W halogen bulb

Feed wire length: 16 inches long

Diameter: 2 1/8", **Height:** 3/4"

STRONG ADVANTAGES:

With built-in constant voltage LED circuit board, powered by 10-30VDC.

Adopts 24-SMD NICHIA LED to guarantee high brightness and low working temperature.

Warm White: 3000°K | Cool White: 6000°K

Plastic front lens matte

FINISHES:

FL-1207 02 WW (White Body, Warm White LED)

FL-1207 02 W (White Body, Cool White LED)

FL-1207 05 WW (Silver Body, Warm White LED)

FL-1207 05 W (Silver Body, Cool White LED)

COMPATIBLE LED DRIVERS:

LED-10W 12VDC (10W, Input 120V 50/60Hz, Output 12VDC Non-Dimmable)

LED-25W 12VDC (25W, Input 85V-277V 50/60Hz, Output 12VDC Non-Dimmable)

LED-60W 12VDC (60W, Input 100-277V 60Hz, Output 12VDC Non-Dimmable)

LED-100W 12VDC (100W, Input 120-277V 50/60Hz, Output 12VDC Waterproof Non-Dimmable)

FL-50W-12V-LED-DIM (50W, Input 120V 50/60Hz, Output 12VDC Non-Dimmable)

FL-60W-LED-PLUGIN (60W, Input 100-240V 50/60Hz, Output 12VDC Non-Dimmable)

FL-1206T (60W, Input 120-240V 50/60Hz, Output 12VDC Waterproof Non-Dimmable)

FL-1210W (100W, Input 120-240V 50/60Hz, Output 12VDC Waterproof Non-Dimmable)

FL-1220W (200W, Input 120-240V 50/60Hz, Output 12VDC Waterproof Non-Dimmable)